



Cadillac Products Packaging Company

PRODUCT INFORMATION BULLETIN

CADPAK HD200

QPL MIL-PRF-131K

**Super Heavy Duty Barrier Packaging:
Watervaporproof, Greaseproof, Flexible, Heat-Sealable**

**Structure description: Biax Nylon/PE/Cross-Lam PE/PE/Foil/Heavy
Duty Coex**

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUES	UNITS	TEST METHOD
Caliper	10.3	mil	ASTM D2103
Yield	2,650	in ² /lb	Calculated
Puncture Resistance	40	lbs	FED STD 101
Tensile Strength	48	lbs/in	ASTM D882
Tear Strength	>1,000	grams	ASTM D1922
OTR	0.0005	cc/100 in ² /day @0% RH, 23°C	ASTM D3985
WVTR	0.0005	g/100 in ² /day @ 90% RH 40°C	ASTM F1249
Seal Strength	23	lbs/in	ASTM F88
Suggested Sealing Conditions	435°F, 60psi, 3.0sec		

01/30/08:9998-HD200

The information on this data sheet has been established by company based laboratory testing. This information does not imply warranty by Cadillac Products Packaging Co. for product specifications, tolerances, or function in the end use.

This document is confidential and may be legally privileged. If you are not an intended recipient or an authorized representative of an intended recipient, you are prohibited from using, copying or distributing the information in this document.