



Cadillac Products Packaging Company

PRODUCT INFORMATION BULLETIN

CADPAK CL

TRANSPARENT HIGH BARRIER PACKAGING
QPL MIL-PRF-22191F, Type 1, Class 1 (Unlimited Use)

Watervaporproof, Greaseproof, Flexible, Heat-Sealable

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUES	UNITS	TEST METHOD
Caliper	4.0	mil	ASTM D2103
Yield	6,300	in ² /lb	Calculated
Puncture Resistance	21	lbs	FED STD 101
Tensile Strength MD/TD	37/28	lbs/in	ASTM D882
OTR	0.010	cc/100 in ² /day @0% RH, 23°C	ASTM D3985
WVTR	0.003	g/100 in ² /day @ 90% RH 40°C	ASTM F1249
Seal Strength	18	lbs/in	ASTM F88
Suggested Sealing Conditions	375°F, 40psi, 2.0sec		

03/05/09:3000-CL

The information on this data sheet has been established by company based laboratory testing. This information does not imply warranty by Cadillac Products Packaging Co. for product specifications, tolerances, or function in the end use.

This document is confidential and may be legally privileged. If you are not an intended recipient or an authorized representative of an intended recipient, you are prohibited from using, copying or distributing the information in this document.